

Dry Bath



Option accessories: W7.6xD10.1xH5cm

MODEL	OD(mm)	Capacity	MODEL	OD(mm)	Capacity
DBB-080	8	30	DBB-180	18	12
DBB-110	11	24	DBB-210	21	12
DBB-120	12	20	DBB-240	24	6
DBB-150	15	12	DBB-250	25	6
DBB-165	16.5	12	DBB-300	30	6



Specifications:

MODEL	130-1	130-2	200-1	200-2
Temperature				
Working range	Ambient+5°C~130°C		Ambient+5°C~200°C	
Stability	± 0.1°C~±0.4°C			
Controller	Microprocessor based P.I.D control			
Sensors	PT 100Ω			
Heater	200W	400W	200W	400W
Timer	0~9999 mins or 0~9999 hours. Could be setting delay on or delay off			
Dimension (cm)				
Chamber	W10.5/D7.8/H5	W15.2/D10.5/H5.0	W10.5/D7.8/H5.0	W15.2/D10.5/H5.0
Overall	W21.5/D28/H9.3	W21.5/D28/H9.3	W20.5/D22.5/H15.5	W25/D25.5/H15.5
Power source	110/220V 50/60Hz 2/1A	110/220V 50/60Hz 4/2A	110/220V 50/60Hz 2/1A	110/220V 50/60Hz 4/2A
Weight	3 kg	3 kg	4.2 kg	5 kg

COD Dry Bath



MODEL	COD-25
Temp. range	Ambient+5°C~200°C
Temp. Stability	± 0.1°C~±0.4°C
Timer	0~9999 mins or 0~9999 hours. Could be setting delay on or delay off
Dimension (cm)	
Block	W11.5/D11.5/H6 (φ16.5mm*25 pcs)
Overall	W20.5/D25/H12
Power source	110V/220V 60/50Hz 2/1A
Weight	kg

DRY BATH 130/200 SYSTEM

誠信 / 負責 / 專業 / 服務

明頂科技有限公司

TEL.07-552-6160 FAX.07-586-6000

[http:// www.mding.com.tw](http://www.mding.com.tw)

