


Brookfield brings full compliance to stand-alone instruments

DVNe^{xt}

RHEOMETER

- Quick Set up with new Viscosity Wizard and Digital Leveling
- Ethernet and LIMS Connectivity
- Single-handed Spindle Installation and Removal
- Compliant to 21 CFR Part 11 in Stand-alone Mode



DVNext™ RHEOMETER

The all-in-one tool for measuring viscosity and yield stress while complying with 21CFR Part 11 and GAMP



FEATURES

Cone/Plate Version

7-inch Full Color Touch Screen Display

Enhanced Controls
Real Time Graphing
Supports Multiple Languages

Displayed Info:

- Viscosity (cP or mPa·s)
- Temperature (°C or °F)
- Shear Rate/Stress
- % Torque
- Speed/Spindle
- Step Program Status
- Math Model Calculations

Viscosity Wizard

Built-in math models for data analysis in stand-alone mode. E.g. Casson, Bingham, Power Law, Thix Index

Integrated Temperature Control with connection to AMETEK Brookfield TC series Baths and AP/SD Controllers or AMETEK Brookfield Thermosel System.

Stand-alone programming

RTD Temperature Probe

Accuracy: ±1.0% of range
Displayed with test data

Repeatability: ±0.2%

Analyze characteristics such as yield stress, flow curves (mixing, pumping, spraying), leveling and recovery

USB PC Interface provides optional computer control and automatic data collection capability

Digital Leveling

Internal Data Storage: 150 MB

GAMP

21 CFR Part 11 Compliant

Customizable User Access
Date and Time Stamp File
Electronic Signatures
Uneditable PDFs
Automated Archived Audit Trail

Built-In Options

Math Modeling
Temperature Control
Yield Tests
Programmable QC Limits, Alarms and End Conditions

WHAT'S NEW?

Viscosity Wizard

To be up and running quickly

Digital Leveling

To ensure when testing you are always level

Automated Oscillation Test

Confirms proper operation

Ethernet Connectivity

For ease of saving your data

LIMS Connectivity

Always have your data where you need it

Compliance to 21 CFR Part 11

In Stand-alone mode

Magnetic Coupling System

For quick one handed installation and removal of spindles

Barcode Scanning

To make work easier and accurate

Updated Gap Setting in Cone/Plate versions

Gel Timer Functions

In standard configurations

OPTIONAL ACCESSORIES

RheocalcT Software

Label Printer

Bar Code Scanner

Vane Spindles

Ball Bearing Suspension
(standard in high torque instruments)

Viscosity Standards

RV/HA/HB-1 Spindle

Magnetic Coupling System

Quick Action Lab Stand

Temperature Bath

Small Sample Adapter

UL Adapter

Thermosel

Helipath Stand with T-bar Spindles

Spiral Adapter

DIN Adapter

Gel Timer Specific Coupling Assembly

VISCOSITY RANGE

cP (mPa·s)

SPEEDS

(2600 available)

MODEL	Min.	Max.	RPM	Number of Increments
DVNXLV	1†	6M	.01-250	2.6K
DVNXRV	100††	40M	.01-250	2.6K
DVNXHA	200††	80M	.01-250	2.6K
DVNXHB	800††	320M	.01-250	2.6K

†1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles.
†† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.
B = 1 billion M = 1 million K = 1 thousand cP = Centipoise
mPa·s = Millipascal*seconds

