

TAIWAN -20~100°C 低溫循環水槽



MDB401L

MDB402L

MDB403L

Specifications:

MODEL	MDB401L/MDB401H	MDB402L/MDB401H	MDB403L/MDB403H
Temperature			
Working range	-20°C~ 100°C/0°C~100°C	-20°C~ 100°C/0°C~100°C	-20°C~ 100°C/0°C~100°C
Stability	± 0.1°C	± 0.1°C	± 0.1°C
Setting & readout	Digital	Digital	Digital
Heater	1KW	1KW	1.5KW
Cooling Capacity (at 20°C)			
BTU/hr	2400	3000	6000
Kcal/hr	600	750	1500
Watts	697	872	1744
Stirring	By built-in Circulating Pump		
Pumping flow	7 Liters/min. 0.2Kg/cm ²		
Capacity	6.7 Liters	11.7 Liters	20 Liters
Dimension (cm)			
Lid opening	W11.5 x D10	W15 x D15	W20 x D23
Reservoir	W16 / D28 / H15	W21 / D31 / H17	W22 / D41 / H22
Overall	W27 / D43 / H57	W30.5 / D46.5 / H60	W33 / D56 / H75
Power source	110/220V 60/50Hz 14/7A	110/220V 60/50Hz 14/7A	220V 60/50Hz 8A
Weight	35 kg	40 kg	50 kg

明頂科技有限公司

TEL.07-552-6160

FAX.07-586-6000

<https://www.mding.com.tw>